



DECLARATION OF PERFORMANCE

NO. 91003601-CPR-20260310	
1. Unique identification code of the product type	Scan 1003 CS
2. Intended use(s)	Solid fuel burning appliances
3. Manufacturer / trade mark	Jøtul AS Postboks 1411 1602 Fredrikstad, Norway
4. Authorised representative	-
5. System(s) of assessment and verification of constancy of performance of the construction product	System 3
6. The notified test laboratory has performed the initial test according to system 3 Notified body	NB No 1235 (DTI) CPR-1235-ELAB-2718-REV.2
7. Harmonised technical specifications	EN 16510-1:2022, EN 16510-2-2:2022
8. Essential characteristics	
Safety in case of fire*	
Minimum distance to combustible materials - below the bottom (not regarding feet)	$d_B = 0$ mm
Minimum distance to combustible materials - front to the bottom front radiation area	$d_F = 0$ mm
Minimum distance to combustible materials - ceiling	$d_C = 1010$ mm
Minimum distance to combustible materials - rear	$d_R = 225$ mm
Minimum distance to combustible materials - side	$d_S = 500$ mm
Minimum distance to combustible materials - front to the side front radiation area	$d_L = 0$ mm
Minimum distance to adjacent combustible materials (e.g. furniture)	$d_P = 1400$ mm
Material type and thickness of the protective insulation material	Calcium silicate boards, $s = 50$ mm
Hygiene, health and environment	
Emissions at nominal heat output	
Carbon monoxide emission (CO)	781 mg/Nm ³
Nitrogen oxides emission (NO _x)	95 mg/Nm ³
Emission of organic gaseous carbon (OGC)	35 mg/Nm ³
Particulate matter emissions (PM)	17 mg/Nm ³
Emissions at part load heat output	
Carbon monoxide emission (CO)	NPD
Nitrogen oxides emission (NO _x)	NPD
Emission of organic gaseous carbon (OGC)	NPD
Particulate matter emissions (PM)	NPD



* The distances apply to stoves without insulated flue pipe



DECLARATION OF PERFORMANCE

Safety and accessibility in use		
Data for installation to a chimney at nominal heat output		
Flue gas outlet temperature	315 °C	
Minimum flue draught	12 Pa	
Flue gas mass flow	8.1 g/s	
Data for installation to a chimney at part load heat output		
Flue gas outlet temperature	NPD	
Minimum flue draught	NPD	
Flue gas mass flow	NPD	
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T400 G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal heat output		
Space heat output	7.8 kW	
Water heat output (if available)	NPD	
Efficiency	79 %	
Appliance's thermal output and energy efficiency at part load heat output		
Space heat output	NPD	
Water heat output (if available)	NPD	
Efficiency	NPD	
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output	69 %	
Energy Efficiency	Energy Efficiency Index (EEI)	105
	Energy Efficiency Class	A
Electric power consumption at appliance's nominal heat output (if available)	NPD	
Electric power consumption at appliance's part load heat output (if available)	NPD	
Power consumption in standby mode (if available)	NPD	
Sustainable use of natural resources		
Environmental sustainability	NPD	
9.	The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.	

„NPD“ (No Performance Determined), if no quality is stated

Signed on behalf of the manufacturer	
Place and date of issue	Fredrikstad, Norway 10.03.2026
	 Lena Bergqvist (COO)