## DECLARATION OF PERFORMANCE (DOP)

|    | NO. 91006604 CPR-20200303  |  |
|----|--|--|
| 1. | Product Type:  | Freestanding stove Scan 1006-B<br>Ceramic stone  |
| 2. | Type, batch or serial number:  | Scan 1006-B CS   |
| 3. | Intended use of the product:   | Heat distribution/room heating<br>Without hot water supply<br>Fuel type: Wood  |
| 4. | Name and Address of the manufacturer:  | Scan A/S<br>Damsbovej 1<br>5492 Vissenbjerg  |
| 5. | Contact address:   | No relevance   |
| 6. | AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V  | System 3   |
| 7. | Notified body: Test report no:   | DTI<br>NB-No 1235<br>300-ELAB-2326-EN REV. 1<br>300-ELAB-2184-EN SIK-REV. 3  |
| 8. | Declared performance   |  |
|    | Harmonized technical specification   | EN 13240:2001/A2:2004/AC:2007  |
|    | Essential characteristics  | Performance  |
|    | Essential characteristics  | remonitalice   |
|    | Fire safety  Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  |
|    | Fire safety Reaction to fire Distance to combustible materials   | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500   |
|    | Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out  | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³]   |
|    | Fire safety  Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products   | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³]                             |
|    | Fire safety  Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products  Surface temperature  | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³]                             |
|    | Fire safety  Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products  Surface temperature  Electrical safety   | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³] Pass -                      |
|    | Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products  Surface temperature  Electrical safety  Cleanability  Maximum water operating pressure  Flue gas temperature at nominal heat output [EN]  | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³] Pass - Pass                 |
|    | Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products  Surface temperature  Electrical safety  Cleanability  Maximum water operating pressure  Flue gas temperature at nominal heat output [EN]  Mechanical resistance (to carry a chimney/flue) | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³] Pass - Pass - T [227°C] NPD |
|    | Reaction to fire Distance to combustible materials  Risk of burning fuel falling out  Emission of combustion products  Surface temperature  Electrical safety  Cleanability  Maximum water operating pressure  Flue gas temperature at nominal heat output [EN]  | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1500 No  CO [887 mg/Nm³] NOx [95 mg/Nm³] OGC [37 mg/Nm³] Staub [19 mg/Nm³] Pass - Pass - T[227°C]      |

## DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

## Signed on behalf of the manufacturer:

Brian Steen Ørum (Senior Project Manager)

Vissenbjerg, 03.03.2020

SCAN

