TECHNICAL PARAMETERS FOR SOLID FUEL LOCAL SPACE HEATERS EU 2015/1186 OF 24. APRIL 2015

Model identifier(s): Scar		IE						
Indirect heating functionality				No				
Direct heat output(kW)				6.5				
Indirect heat output(kW)				N.A				
Fuel				Preferred fuel (only one) Model identifier(s)				
Wood logs with moisture content \leftarrow 25%				Yes	No	No		
Compressed wood with moisture content < 12%				No	No	No		
Other woody biomass				No	No	No		
Anthracite and dry steam coal				No	No	No		
Hard coke				No	No			
Low temperature coke				No	No	No		
Bituminous coal				No	No	No		
Lignite briquettes				No	No	No		
Peat briquettes				No	No	No		
Blended fossil fuel briquettes				No	No	No		
Other fossil fuel				No	No	No		
Blended biomass and fossil fuel briquettes				No	No	No		
Other blend of biomass and solid fuel				No	No	No		
Characteristics when op	erating with	the prefer	red fuel					
Seasonal space heating	energy effic	iency η₅ [%]		-				
Energy Efficiency Class				A+				
Energy Efficiency Index (EEI)				116				
ltem	Symbol	Value	Unit	ltem	Symbol	Value	Unit	
Heat output	/			Use efficiency (NCV as red		/ /		
Nominal heat output	P _{nom}	6.5	kW	Useful efficiency at nominal heat output	$\eta_{_{th,nom}}$	86	%	
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{_{th,min}}$	N.A.	%	
Auxiliary electricity consumption				Type of heat output/roor	n temperat	ure control (select one)	
At nominal heat output	el _{max}	x,xxx	kW	single stage heat output, no room temperature control		[yes/no]		
At minimum heat output	el _{min}	x,xxx	kW	two or more manual stages, no room temperature control		[yes/no]	Yes	
In standby mode	el _{sb}	x,xxx	kW	with mechanic thermostat room temperature control		[yes/no]		
				with electronic room temperature control		[yes/no]		
				with electronic room temperature control plus day timer		[yes/no]		
		with electronic room temperature control plus week timer		perature	[yes/no]			
				Other control options (mi	ultipl <u>e selec</u> t	tions <u>possible</u>)	
				room temperature control, with presence detection		[yes/no]		
				room temperature contro open window detection	[yes/no]			
				with distance control opt	tion	[yes/no]		
Permanent pilot flame p	ower requir	eme <u>nt</u>						
Pilot flame power re- quirement (if applicable)	P _{pilot}	N.A.	kW		Λ			
Contact details	Name and address of the supplier: Brian Ørum, R&D Manager, Scan A/S, Denmark							