Model identifier(s): Scan 1004 CS-HE									
Indirect heating functionality				No					
Direct heat output(kW)				9					
Indirect heat output(kW)				N.A					
				Preferred fuel Model		Emissions from space heating at nominal heat output			
			PM			OGC	CO	NO <sub>x</sub>	
Fuel				(Only one)	identifier(s)	[X] mg/Nn	n <sub>3</sub> (13 % C	D <sub>2</sub> )	· · · · · · · · · · · · · · · · · · ·
Wood logs with moisture content ← 25%				Yes	No	29	59	1105	83
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when operating with the preferred fuel									
Seasonal space heating energy efficiency $\eta_s$ [%] 76									
Energy Efficiency Class A+									
Energy Efficiency Index (E	115								
ltem	Symbol	Value	Unit	lt.	Symbol	Symbol Value		Unit	
Heat output				<b>Use efficiency</b> (NCV as re		ceived)			
Nominal heat output	$P_{nom}$	9	kW	Useful efficiency at nominal heat output		$\eta_{th, nom}$ 86		5	%
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful effic minimum he output (ind	eat <sup>'</sup>	η <sub>th, min</sub>	N.A.		%
Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
At nominal heat output	el <sub>max</sub>	x,xxx	kW	single stage temperatur	no room [yes,			ĺ	
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more	s, no l	[yes/no		Yes	
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mecha temperatur	t room	[yes/no]			
				with electro	oerature	[yes/no]			
				with electro control plus	perature	[yes/no]			
				with electro control plus	oerature	[yes/no]			
				Other cont	ultiple sele	ctions po	ssible)		
				room tempo presence do	l, with	[yes/	'no]		
				room tempo open windo	l, with	[yes/no]			
				with distan	on	[yes/	no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW						
Name and address of the supplier:  Contact details  Brian Ørum, R&D Manager, Scan A/S, Denmark									